# **Material Safety Data Sheet**

IDENTITY (as Used on Label and List)					
Metal Clay Powder – Bronze					
Section I			alambana Nijinal		
Manufacturer's Name		Emergency Telephone Number			
Hadar Jacobson DBA Textures		(510) 528 4193			
Address (Number, Street, City, State and ZIP Code)		Telephone Number for Information: (510) 528 4193			
918 Ventura Avenue		Date Prepared: 03/15/2009			
Berkeley, CA 94707-2123					
Section II—Hazardous Ingredients/Ident Hazardous Components (Specific Chemical Iden					
Name(s))	OSHA PEL	ACGIH TLV		% (optional)	
Copper (CAS 7440-50-8)		1 mg/m³	1 mg/m <sup>3</sup> 1 mg/m <sup>3</sup> (dust) 0.1 mg/m <sup>3</sup> (fume)		35-89.1%
Tin (CAS 7440-31-5)	2 mg/m <sup>3</sup>			9.9-35%	
Proprietary Binder		1 mg/m <sup>3</sup>	1 mg/m <sup>3</sup>		1-30%
Section III—Physical/Chemical Character	eristics				
Boiling Point	Unknown	Specific Gravity	Specific Gravity (H <sub>2</sub> 0 = 1)		Unknown
Vapor Pressure (mm Hg)	Unknown	Melting Po	oint		Unknown
Vapor Density (AIR = 1)	Unknown	Evaporation	on Rate (B	utyl	Unknown
		Acetate =	1)		
Solubility in Water: Copper and	l tin are insolu	ble; Proprieta	ary Binder	solubility	is limited by
viscosity.		•	•	_	·
Appearance and Odor: Odorles	ss, chocolate-l	prown powde	er.		
Section IV—Fire and Explosion Hazard		· · ·			
Flash Point (Method Used)		Flammabl	e LEL		UEL
N/A			Unk	nown	
N/A		Limits	UIIN	HOWH	Unknown
	rav dry chemi				Unknown an extinguishing
Extinguishing Media: Water sp	•	cal, foam, ca			
Extinguishing Media: Water spagents may be used on fires in	volving this pr	cal, foam, ca oduct.	rbon dioxid	de or clea	an extinguishing
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure	volving this pres: Use self-co	cal, foam, ca oduct.	rbon dioxid	de or clea	an extinguishing
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed ar	volving this press: Use self-coess.	cal, foam, ca oduct. ontained brea	athing appa	de or clea	d full protective
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production	volving this press: Use self-coess.	cal, foam, ca oduct. ontained brea	athing appa	de or clea	d full protective
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed ar Hazardous Combustion Productionide and smoke.	volving this press: Use self-coeas.  cts: Combustic	cal, foam, ca oduct. ontained brea on products i	athing appa	de or clea	d full protective
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production dioxide and smoke.  Unusual Fire and Explosion Hazardous Combustion Production Prod	volving this property uses: Use self-contents.  ets: Combustications.	cal, foam, ca oduct. ontained brea on products in charges gene	athing apparently athing apparently athing apparently at the second seco	de or clear aratus an bon mon mptying	d full protective oxide, carbon package in or
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production dioxide and smoke.  Unusual Fire and Explosion Hanear flammable vapors may care	volving this property uses: Use self-contents.  ets: Combustications.	cal, foam, ca oduct. ontained brea on products in charges gene	athing apparently athing apparently athing apparently at the second seco	de or clear aratus an bon mon mptying	d full protective oxide, carbon package in or
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Productionide and smoke.  Unusual Fire and Explosion Hanear flammable vapors may case Section V—Reactivity Data	volving this press: Use self-coleas. ets: Combusticated Static coleans are flash fire.	cal, foam, ca oduct. ontained brea on products in charges gene May form fla	athing appa nclude: car erated by e	de or clea aratus an bon mon mptying ust-air mi	d full protective oxide, carbon package in or
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production dioxide and smoke.  Unusual Fire and Explosion Hanear flammable vapors may casection V—Reactivity Data  Stability: Stable.	volving this press: Use self-coeas. cts: Combusticutards: Static cuse flash fire.	cal, foam, ca oduct. ontained brea on products in charges gene May form fla	athing apparently athing apparently articles are the services are the serv	de or clear aratus and bon mon mptying ust-air mi known.	d full protective oxide, carbon package in or xtures.
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production dioxide and smoke.  Unusual Fire and Explosion Hanear flammable vapors may case Section V—Reactivity Data  Stability: Stable.  Incompatibility (Materials to Av.)	volving this press: Use self-coeas. ets: Combustic starts: Static couse flash fire.  Coroid): Strong al	cal, foam, ca oduct. ontained brea on products in charges gene May form fla anditions to Av kalies, chlora	athing apparently athing apparently athing apparently athing apparently athing apparently athing apparently athing apparently athing athing apparently athing at a second at a secon	de or clear aratus an bon mon mptying ust-air mi known. ates, min	an extinguishing d full protective oxide, carbon package in or xtures.
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production dioxide and smoke.  Unusual Fire and Explosion Hanear flammable vapors may can section V—Reactivity Data  Stability: Stable.	volving this press: Use self-coeas. ets: Combustic starts: Static couse flash fire.  Coroid): Strong al	cal, foam, ca oduct. ontained brea on products in charges gene May form fla anditions to Av kalies, chlora	athing apparently athing apparently athing apparently athing apparently athing apparently athing apparently athing apparently athing athing apparently athing at a second at a secon	de or clear aratus an bon mon mptying ust-air mi known. ates, min	an extinguishing d full protective oxide, carbon package in or xtures.
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production of Explosion Production and Section V—Reactivity Data  Stability: Stable.  Incompatibility (Materials to Average Hazardous Decomposition or Ecopper compounds.	volving this press: Use self-coeas. cts: Combustic cuse flash fire.    Coroid): Strong all syproducts: De	cal, foam, ca oduct. ontained brea on products in charges gene May form fla nditions to Av kalies, chlora ecomposition	athing apparently athing apparently athing apparently athing apparently athing apparently athing apparently athing at a second at a sec	de or clear aratus an bon mon mptying ust-air mi known. ates, min hydroge	d full protective oxide, carbon package in or xtures.
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Production of the enclosed and smoke.  Unusual Fire and Explosion Hamer flammable vapors may can section V—Reactivity Data  Stability: Stable.  Incompatibility (Materials to Avance) Hazardous Decomposition or English in the enclosed and smoke.	volving this press: Use self-coeas. cts: Combustic cuse flash fire.    Coroid): Strong all syproducts: De	cal, foam, ca oduct. ontained brea on products in charges gene May form fla anditions to Av kalies, chlora	athing apparently athing apparently athing apparently athing apparently athing apparently athing apparently athing at a second at a sec	de or clear aratus an bon mon mptying ust-air mi known. ates, min hydroge	an extinguishing d full protective oxide, carbon package in or xtures.
Extinguishing Media: Water spagents may be used on fires in Special Fire Fighting Procedure clothing for fires in enclosed and Hazardous Combustion Productionide and smoke.  Unusual Fire and Explosion Hanear flammable vapors may case Section V—Reactivity Data  Stability: Stable.  Incompatibility (Materials to Avaluated Hazardous Decomposition or Ecopper compounds.	volving this press: Use self-coeas. cts: Combustic vards: Static couse flash fire.  Coroid): Strong all syproducts: Desired Coro	cal, foam, ca oduct. ontained brea on products in charges gene May form fla nditions to Av kalies, chlora ecomposition	athing apparently athing apparently athing apparently athing apparently athing apparently athing apparently athing at a second at a sec	de or clear aratus an bon mon mptying ust-air mi known. ates, min hydroge	d full protective oxide, carbon package in or xtures.

#### Section VI—Health Hazard Data

Target Organs: Respiratory system, nasal septum, skin, eyes, gastrointestinal, kidneys, liver, vardiovascular system.

Primary entry routes: Inhalation, ingestion, skin or eye contact.

#### **Health Effects**

Copper dusts and mists are eye and mucous membrane irritants, primary skin irritants and skin sensitizers. Acute exposure may cause metallic taste and nasal ulceration and perforation. Prolonged skin contact may produce sensitization dermatitis. Exposure may result in irritation and metal-fume fever, metallic taste and discoloration of the skin and hair. May cause eye irritation by mechanical abrasion. May cause skin irritation by mechanical abrasion. Inhalation of dust may cause respiratory tract irritation. Ingestion of copper compounds may cause vomiting and collapse. Acute poisoning is characterized by hemolysis, jaundice, anuria, hypotension, and convulsions.

Inorganic tin compounds are eye, mucous membrane and primary skin irritants. Acute exposure may irritate the eyes and respiratory tract. Repeated or prolonged skin contact produces dermatitis.

## **Emergency and First Aid Procedures**

Eye: Contact lenses should not be worn. Hold eyelids apart. Immediately flush eyes with plenty of low-pressure water for at least 15 minutes. Get medical attention if irritation persists.

Skin: Wash with soap and water. Get medical attention if irritation develops or persists.

Inhalation: Move the exposed person to fresh air at once. If breathing has stopped, perform artificial respiration. Keep the affected person warm and at rest. Get medical attention as soon as possible.

Ingestion: Emergency treatment – dilute with water or milk. Remove by gastric lavage (i.e., stomach tube) unless patient is vomiting. Get medical attention as soon as possible. Never give anything by mouth to an unconscious person.

### Section VII—Precautions for Safe Handling and Use

Steps to Be Taken in Case Material Is Released or Spilled: Sweep gently to avoid dust cloud formation. If product is not contaminated, scoop into clean containers for use. If product is contaminated, scoop into containers and dispose appropriately. Avoid wetting spills, as surfaces subject to spills may become slippery. Apply absorbent to wet spills and sweep up gently for disposal.

Handling and Storage: Store in a cool, dry, well-ventilated area at approximately 68°F (20°C). Keep container closed when not in use.

Waste Disposal Method: Dispose of in accordance with local, state, and federal regulations.

Other Precautions: Avoid conditions that generate dust; product may form flammable dust-air mixtures. Avoid emptying package in or near flammable vapors; static charges may cause flash fire. Keep away from heat, flame, sparks and other ignition sources.

## Section VII—Control Measures

#### Personal Protective Equipment:

- Goggles: Safety goggles with side shields, if needed.
- Gloves: Required for those with extreme sensitivity.
- Respirator: Wear supplied air respirator under confined or enclosed spaces, if needed.

Workplace considerations: Eye-wash fountain, soap and water wash station.

Ventilation: Sufficient ventilation, in volume and pattern, should be provided to keep air contamination below current applicable OSHA permissible limits.

**Supplier Notification:** This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of 40 CFR 372:

CAS Number	Chemical name	Percent by Weight
7440-50-8	Copper	35-89.1%

### **Disclaimer of Liability:**

The information provided is based on data furnished to us by our suppliers or determined by in our facilities at the time that this product was formulated. Although believed to be reliable, the information and products are intended for use by skilled persons at their own risk. Users should make their own determinations as to the suitability of the product for their particular use or purpose. NO WARRANTY OF MERCHANTABILITIY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS IMPLIED REGARDING THE ACCCURACY OF COMPLETENESS OF THIS INFORMATION. Seller assumes no responsibility for events resulting or damages incurred from the use of this product and any obligations between seller and buyer are to be controlled by the terms and conditions contained in seller's acknowledgement forms.